



**acontis technologies GmbH**

**SOFTWARE**

# **EC-Monitor**

**Release Notes**

**V3.3.1.02**

**AT3400**

**Edition: April 29, 2026**

EtherCAT® is registered trademark and patented technology, licensed by Beckhoff Automation GmbH, Germany.

© Copyright **acontis technologies GmbH**

Neither this document nor excerpts therefrom may be reproduced, transmitted, or conveyed to third parties by any means whatever without the express permission of the publisher. At the time of publication, the functions described in this document and those implemented in the corresponding hardware and/or software were carefully verified; nonetheless, for technical reasons, it cannot be guaranteed that no discrepancies exist. This document will be regularly examined so that corrections can be made in subsequent editions. Note: Although a product may include undocumented features, such features are not considered to be part of the product, and their functionality is therefore not subject to any form of support or guarantee.

# Contents

<b>1</b>	<b>New Features</b>	<b>4</b>
<b>2</b>	<b>Migration</b>	<b>5</b>
<b>3</b>	<b>Enhancements/bug fixes</b>	<b>8</b>

## 1 New Features

### 1.1 V3.3

- Update to expat V2.6.4
- Simplified clean IoCtl interface
- Application variables can be mapped to “ENI/Process variables”, now (conversions are possible via callbacks)
- New Ethernet real-time driver XDP and DPDK
- Update RtaccWin V1.0.9
- Update atemsys V1.4.32

### 1.2 V3.2

- Codesys EtherCAT® Master support
- KPA EtherCAT® Master support

## 2 Migration

### 2.1 From V3.2

#### 2.1.1 EC-RtEth Real-Time Ethernet Drivers

- Rename EC\_T\_LINK\_PARMS\_EOM::abyIpAddress to abyTargetIpAddress
- Rename EC\_T\_LINK\_PARMS\_EOM::abyDstMac to abyTargetMac
- Add EC\_T\_LINK\_PARMS\_EOM::eNetworkMode
- Add EC\_T\_LINK\_PARMS\_SOCKXDP::eXdpMode
- Remove Dongle licensing via Microchip ATSHA204A for emllGEM (32Bit)

#### 2.1.2 RAS

- Rename EcRasServer.h to EcMonitorRasServer.h
- Rename EcRasClient.h to EcMonitorRasClient.h
- Rename ECMASTERRAS\_T\_CONNOTIFYDESC to EC\_T\_RAS\_CONNOTIFYDESC
- Rename ECMASTERRAS\_T\_REGNOTIFYDESC to EC\_T\_RAS\_REGNOTIFYDESC
- Rename ECMASTERRAS\_T\_MARSHALERRORDESC to EC\_T\_RAS\_MARSHALERRORDESC
- Rename ECMASTERRAS\_T\_NONOTIFYMEMORYDESC to EC\_T\_RAS\_NONOTIFYMEMORYDESC
- Rename ECMASTERRAS\_NOTIFY... to EC\_RAS\_NOTIFY...
- Rename ECMASTERRAS\_ACCESS\_LEVEL... to EC\_RAS\_ACCESS\_LEVEL...
- Add EC\_T\_MBX\_GATEWAY\_SRV\_PARMS::dwStackSize

#### 2.1.3 EC\_IOCTL...

- Refactor emonIoControl() to emonIoCtl() . EC\_T\_IOCTLPARMS removed as all parameters are passed as flattened parameters to emonIoCtl().

#### 2.1.4 EC\_LINKIOCTL...

- Refactor EcLinkIoCtl(). EC\_T\_LINK\_IOCTLPARMS removed as all parameters are passed directly to EcLinkIoCtl.
- Rename EC\_LINKIOCTL\_PROMISCUOUSMODE to EC\_LINKIOCTL\_PROMISCUOUSMODE
- Change EC\_LINKIOCTL\_INTERRUPTENABLE: not the pbyInBuf itself is interpreted/evaluated, but the buffer that is pointed to (... == ((EC\_T\_BOOL)pbyInBuf)). Affected Ethernet real-time drivers are: emllCCAT, emllCPSW, emllEG20T, emllETSEC, emllGEM, emllI8254x, emllIntelGbe, emllL9218i, emllLAN743x, emllRTL8139, emllRTL8169.
- Change EC\_LINKIOCTL\_PROMISCUOUSMODE: not the pbyInBuf itself is interpreted/evaluated, but the buffer that is pointed to (... == ((EC\_T\_BOOL)pbyInBuf)). Affected Ethernet real-time drivers are: emllCCAT, emllETSEC, emllI8254x, emllIntelGbe, emllL9218i, emllRTL8139.

- Change EC\_LINKIOCTL\_GETLINKMODE: not the pbyOutBuf itself is written, but the buffer that is pointed to ( $((EC\_T\_LINKMODE)(pParms->pbyOutBuf)) = \dots$ ). Affected Ethernet real-time drivers are: emlIBPF, emlBcmNetXtreme, emlCCAT, emlEG20T, emlETSEC, emlGEM, emlI8254x, emlIntelGbe, emlI9218i, emlLAN743x, emlRTL8139, emlRTL8169.
- Change EC\_LINKIOCTL\_FORCELINKMODE: not the pbyInBuf itself is interpreted/evaluated, but the buffer that is pointed to ( $\dots == ((EC\_T\_DWORD)pParms->pbyInBuf)$ ). Affected Ethernet real-time drivers are: emlI8254x, emlIntelGbe.
- All Real-Time Ethernet Driver set pdwNumOutData in EC\_LINKIOCTL... set the amount of bytes actually written to pbyOutBuf if pdwNumOutData provided by application.
- Add some missing input parameters checks in Real-Time Ethernet Driver for some EC\_LINKIOCTL...

## 2.1.5 Custom Ethernet real-time drivers

- Refactor PF\_EcLinkIoctl pfEcLinkIoctl to PF\_EcLinkIoctl pfEcLinkIoctl (upper case changed from “Ioctl” to “Ioctl”) with the corresponding flattened parameters.
- All EC\_LINKIOCTL... must set the amount of bytes actually written to pbyOutBuf if pdwNumOutData provided by caller.

## 2.1.6 Binary incompatible structs

The following struct types are not binary compatible with previous versions:

- EC\_T\_CYC\_COPY\_INFO
- EC\_T\_MONITOR\_INIT\_PARMS (dwBusCycleTimeUseC has been removed and completely replace with dwBusCycleTimeNsec)

## 2.1.7 Preprocessor macros and defines

The following deprecated preprocessor macros got removed

- #define FILTVAL 128
- #define OLD\_WEIGHT (FILTVAL-1)
- #define ROUNDINGVAL (FILTVAL/2)
- #define AVG\_MULT (FILTVAL/8)

## 2.1.8 OS Layer

- Rename SafeOs[Free|DeleteEvent|DeleteLock] to OsSafe[Free|DeleteEvent|DeleteLock]
- Remove OsForceThreadPrioNormal use OsCreateThread with desired thread priority or OsSetThreadPriority instead
- Rename and separation of concerns using preprocessor definitions from “EC\_VERSION\_[LINUX|WINDOWS|...]” to “EC\_OS == EC\_OS\_WINDOWS” (and/or “EC\_OS\_VERSION == [WINVER|\_WIN32\_WINNT|\_GLIBC\_|2|3|...]”)
- Remove GO32, RIN32, RTAI, RTXC, XMC

## 2.1.9 Examples

- T\_EC\_DEMO\_APP\_PARMS (dwBusCycleTimeUsec has been removed and completely replace with dwBusCycleTimeNsec)

## 2.2 From V3.1

- Change EC-Monitor API Prefix from “em” to “emon”
- Update to expat V2.4.9
- Remove obsolete .NET and Python interface classes, enums and methods
- Refactor EC\_T\_SB\_MISMATCH\_DESC
- Rename emCoeGetOdList(), emCoeGetObjectDesc() and emCoeGetEntryDesc() to emonCoeGetOdListReq(), emonCoeGetObjectDescReq() and emonCoeGetEntryDescReq()
- Replace emI8254x with emIIntelGbe and support of TTS for Intel® i210 and i211
- Rename emPerfMeasInternal to emPerfMeas, old deprecated API removed

## 3 Enhancements/bug fixes

### 3.1 V3.3.1.02

#### Fixes

- #6750 - Fix truncated strings due to using `OsSafeStrncpy()` / `OsSafeStrncpy2()` with `nLen` instead of `nSize` at some locations (regression since V3.3.0.02)
- #6736 - Fix memory leak in examples using `emllEom`, `emllMultiplier`, `emllVlan`
- #6713 - Fix missing rebuild bus topology on delayed slave communication
- #6734 - Fix truncated data read of Configured address list Objects `0xF02n` and Detected address list Objects `0xF04n` in Master OD using complete access

#### Platform

- #6732 - Fix memory leak in `CreateLinkParmsFromCmdLine...` with invalid parameters

### 3.2 V3.3.1.01

#### Enhancement

- #6699 - Replace `T_EC_DEMO_APP_PARMS::dwBusCycleTimeUsec` with `dwBusCycleTimeNsec`
- #6690 - Remove obsolete performance measurement defines `FILTVAL`, `OLD_WEIGHT`, `ROUNDINGVAL`, `AVG_MULT`
- #6581 - Replace `EC_T_MONITOR_INIT_PARMS::dwBusCycleTimeUsec` with `dwBusCycleTimeNsec`
- #6339 - Unify optional command line parameters usage
- #6224 - Refactor `EC_OS` and `EC_VERSION...` macros
- #5859 - Add `pAppContext` parameter to `EcSelectLinkLayer` functions
- #4177 - Add `..._MBXSND_WKC_ERROR` notifications
- #5757 - Add `emonCoeGetEntryDesc()`, `emonCoeGetObjectDesc()`, `emonCoeGetODList()`
- #6605 - Apply application parameters to linklayer parameters in `SetAppParmsFromCommandLine()` and `SetAppParmsLogging()` instead of `main()`
- #6614 - Add Nvidia Thor support to Fingerprint
- #6682 - Add `emllIntelGbe` for QNX71 ARM\_64Bit

#### Fixes

- #6724 - Fix missing `EcMemoryLog.h` in packages (regression since V3.3.0.02)
- #6641 - Fix crash in `SetAppParmsFromCommandLine()` due to missing null pointer checks
- #6670 - Fix EC-Monitor state flags for device emulation topologies

#### Platform

- #6623 - Remove Dongle licensing via Microchip ATSHA204A for GEM 32Bit
- #6563 - Add support for Microchip ATSHA204A to Fingerprint
- #5235 - Add Software Bill of Materials (SBOM)
- #6064 - Include `EcDemoTimingTaskPlatform.h` through `EcDemoApp.h`

- #6393 - Add ATEMRAS\_NOTIFY\_EXCEPTION
- #6462 - Add support for Link Speed configuration to emllHpe
- #6507 - Update atemsys V1.4.37
  - Fix support for devices with up to 32 clocks to platform / Device Tree Ethernet driver
  - Add support gpio phy reset device tree overlays
  - Fix log level of verbose messages about PCI/PCIe device from INFO to DEBUG
- #6585 - Add i.MX95 support to emllDpdk
- #6591 - Add support for RTOS-32 to emllDW3504
- #6625 - Fix iq-9075 custom parameter in emllDW3504
- #6626 - Add device IDs for I219\_V
- #6644 - Fix performance measurement on VxWorks ARM\_64Bit
- #6647 - Add support for EC\_T\_LINK\_PARAMS\_INTELGBE::linkParams.dwIstStackSize setting to emllIntelGbe in Interrupt Mode
- #6482 - Fix missing files in RAS SDK package (Examples\Common\...)
- #6559 - Remove deprecated “-lang-c++” compiler flag from QNX build
- #6279 - Release libxdp and libbpf in EcLinkClose() in emllSockXdp
- #6495 - Fix erroneous RAS client disconnection with server <= V2.7 due to API timeout (broken since V3.2.2.01)
- #6542 - Fix missing error message on invalid LinkOpen() parameter
- #6633 - Fix MAC Protection for Rockchip RK3588
- #6648 - Add support for QNX8 to emllBpf
- #6659 - Fix send frame occasionally delayed in emllFslFec
- #6674 - Fix emllDW3504 resource leak causing systematic error on subsequent starts
- #6676 - Fix IRQ CPU affinity for Interrupt Mode on VxWorks
- #6680 - Fix missing adapter stop in EcLinkClose() of emllDW3504
- #6716 - Fix incremental cmake build for Linux due to EC\_C\_CXX\_FLAGS recursion (regression since V3.3.0.02)
- #6718 - Fix crash in EcLinkOpen(...) in emllEom, emllRemote, emllSimulator, emllVlan due to name clash (S\_apLinkDesc)

### 3.3 V3.3.0.03

#### Enhancement

- #6506 - Add parameters wMainTapPortIn and wMainTapPortOut to EC\_T\_MONITOR\_INIT\_PARAMS
- #6493 - Add emGetHcGroupInfo() and emGetHcGroupNumOf()
- #6349 - Add support for SwapData strings in ENI according to ETG.2100 V1.0.3
- #5764 - Add EC\_E\_VERSION\_MISMATCH
- #5052 - Add emonBadConnectionsDetect()
- #4177 - Add ...\_MBXSND\_WKC\_ERROR notifications
- #6408 - Enhance master state detection

- #6427 - Enhance emonGetMonitorStatus() to include topology and PDO configuration state
- #6430 - Enable file logging specifically in CEcLogging
- #6505 - Support incomplete topologies

### Fixes

- #6492 - Fix missing reset of emonGetMonitorStatus() topology and PDO configuration state flags
- #6508 - Fix missing update of Inputs.BusTime in process data image
- #6532 - Fix acyclic frame detection

### Platform

- #6554 - Add support for RISC-V to emllEom on Linux
- #6571 - Bump minimum CMake version to 3.14
- #6502 - Refactor MacOS workspaces to match generic structure
- #6303 - Add fingerprint support to emllLAN743x
- #5832 - Add ROS2 support
- #5576 - Add support for SSL/TLS to RAS
- #6184 - Update emllTiEnetIcsg to TI SDK11
- #6236 - Add support for Microchip PolarFire to emllGEM
- #6238 - Add support for emllTemac
- #6271 - Fix emllCPSWG performance issues on TI Jacinto TDA4VM
- #6301 - Add support for Rockchip RK3506, Allwinner T153 and T527 to emllDW3504
- #6428 - Update RtaccWin V1.1.1
- #6436 - Add Interrupt Mode for emllDW3504
- #6484 - Add emllVlan to Windows
- #6317 - Add support for Qualcomm IQ-9075 to emllDW3504
- #6550 - Fix crash in OsGetLinkLayerRegFunc(EC\_T\_CHAR\* szDriverIdent, EC\_NULL)
- #6488 - Remove faulty signature check in emllMultiplier EcLinkIoCtl() (regression since V3.3.0.01)
- #6036 - Add workaround for I210 Errata 25 (Slow System Clock) to emllIntelGbe on VxWorks7
- #6472 - Fix unexpected MAC address when using multiple instances of emllDW3504 simultaneously
- #6483 - Fix crash in emllVlan EcLinkRecvFrame() (regression since V3.2.2.04)
- #6534 - Fix emllDW3504 support for RK3576
- #6546 - Fix sending of frames longer than 768 bytes on emllCPSWG
- #6547 - Fix link reconnect with short cycle time for emllCPSWG

## 3.4 V3.3.0.02

### Enhancement

- #6120 - Rename SafeOs[FreeDeleteEvent|DeleteLock] to OsSafe[FreeDeleteEvent|DeleteLock]
- #6013 - Add emGetProcessVarInfoEx() and emGetProcessVarInfoNumOf()
- #5969 - Generalize Windows project properties
- #5865 - Add emGetLicenseFingerprint()
- #5757 - Add emCoeGetEntryDesc(), emCoeGetObjectDesc(), emCoeGetODList()
- #4079 - Add EcMonitorDemoGuiDotNet
- #5687 - Add emGetCfgSlaveSmInfo()
- #5740 - Add EC-Monitor support for EtherCAT Masters without ENI
- #5913 - Add EcMonitorDemoMqttServer
- #6053 - Add ENI Builder(EBI) export
- #6119 - Improve bus scan compatibility with third party EtherCAT Masters
- #6161 - Add support for packet capture files with LINKTYPE\_ETHERNET\_MPACKET(IEEE 802.3 mPackets)
- #6205 - Add support for Fingerprint to SetLicenseKey()
- #6247 - Add EC-Monitor CoE support without ENI
- #6256 - Optimize EtherCAT command processing

### Fixes

- #6316 - Always use EC\_T\_MBXTFERDESC::dwMaxDataLen for mailbox uploads
- #6268 - Remove support for Hilscher netANALYZER
- #6122 - Fix truncated lines in log file about skipped/dropped messages in examples
- #6171 - Fix PDO mapping related prints of object dictionary in examples
- #6226 - Fix malformed packet handling
- #6248 - Rename EcMonitorDemoMqttServer to EcMonitorDemoMqtt
- #6253 - Rename CpcapRecorder::InitInstance(...) to CpcapRecorder::StartPcapRecorder(...) (fix overloaded-virtual warning)

### Platform

- #6379 - Remove OsForceThreadPrioNormal function and SetPriorityClass() calls from libraries
- #6123 - Add support for Renesas RZ/G2L to emllSHeth
- #5902 - Add connection token to RAS
- #5819 - Remove bpf dependency from emllSockXdp
- #5774 - Add emllHpe for INtime
- #5849 - Add support for AllWinner T536 to emllDW3504
- #5879 - Add support for iMX8 on uC3
- #6048 - Add ZEROCOPY Driver mode to emllSockXdp
- #6139 - Update RtaccWin V1.1.0
- #6144 - Add support for Intel Alder-Lake to emllDW3504
- #6153 - Add EC\_LINKIOCTL\_GET\_INTELGBE\_STATISTICS to emllIntelGbe

- #6156 - Add OsPlatformMemoryBarrier() for x86\_64Bit and ARM\_64Bit
- #6198 - Rename Xilinx GEM to Cadence GEM/MACB
- #6280 - Add support for Ti DP83869 to PhyLib
- #6282 - Add full scan of Mdio bus in PhyLib
- #6352 - Add RTL8126 support to emllRTL8169
- #6404 - Set calling convention for LinkLayerReg functions
- #6324 - Fix build errors with musl toolchain on Linux
- #5960 - Fix gcc 13.3 compiler warnings
- #5791 - Fix card specific control access and configuration for I210-I350 in emllIntelGbe
- #6116 - Add bDisableForceBroadcast to emllHpe
- #6160 - Fix thread priority class setting in OsCreateThread() on Windows
- #6162 - Fix print performance histogram on console for FreeRTOS
- #6169 - Fix occasional wrong link status disconnected in emllETSEC
- #6192 - Fix project files for uC3 on iMX8
- #6239 - Reset adapter if RX or TX disabled on reconnection in emllRTL8169
- #6269 - Fix RtaccDevice driver eval version in protected Real-time Ethernet Driver packages
- #6281 - Fix SGMII support for all instances emllGEM
- #6305 - Add signature check for pvInstance parameter to EcLinkFreeSendFrame() in emllIntelGbe
- #6320 - Add bEalInitDeinitByApp to emllDpdk
- #6358 - Update atemsys V1.4.36
  - Fix PCI MSI interrupt broken since V1.4.35 for Kernel >= 6.0.00
- #6183 - Update atemsys V1.4.35
  - Add driver initialization entry point for Kernel >= 6.6.00
  - Fix Xenomai 3.3
  - Fix CPSWG for Kernel >= 6.12
  - Add RiscV support
  - Fix PCI IO memory resource management Kernel >= 6.0.00
- #6135 - Update atemsys V1.4.34
  - Fix for platform devices without 32-bit DMA
  - Add Device Tree Ethernet driver support for Raspberry Pi 5
  - Fix non-PCI IO Memory for PCI devices
- #6380 - Fix EC\_NOTIFY\_SB\_EEPROM\_ACCESS\_DENIED is printing Unknown Text instead of the right notification text
- #6392 - Fix CEcMasterDotNet.Init() returns EC\_E\_NOTSUPPORTED after Init() and Deinit() called several times

## 3.5 V3.3.0.01

### Enhancement

- #5913 - Add EcMonitorDemoMqttServer
- #5802 - Add performance measurement jobs MON\_FrameRoundTripTime and MON\_MasterCycleTime
- #5690 - Rename libEcMaster.a, ... to libEcMasterStatic.a on Linux, Xenomai, ...
- #5062 - Add emLinkInputVarByName(),... to map ENI variables to local application variables
- #4684 - Add EC-Monitor QuickStart Guide
- #5687 - Add emGetCfgSlaveSmInfo()
- #5804 - Add support for EtherCAT open mode
- #5870 - Add eCnfType\_FileByApp to emConfigureNetwork()
- #5911 - Add instance, mode to command line parameters for emIldpdk
- #5912 - Add T\_EC\_DEMO\_APP\_PARMS::dwJobsThreadPrio, dwJobsThreadStackSize
- #5949 - Report missing DLLs in EC-Wrapper
- #5950 - Add histogram export to EC-Wrapper examples
- #6072 - Add support for legacy parameters to emonInitMonitor()

### Fixes

- #6086 - Fix emonCoeSdoUpload() return codes for non-existing objects
- #5897 - Fix hot-connect slave detection with SuperSetENI
- #5834 - Fix process data image in case of TAP inside topology
- #5763 - Add support for random periodic frame loss simulation to esSetErrorGenerationAtSlavePort()
- #5886 - Fix EC\_TRUE and EC\_FALSE macro comments
- #5900 - Fix emCoeGetODList() delivering 0xAnnn objects for unexpected bus slaves
- #5915 - Fix ENI parser error handling
- #5941 - Fix command line parameter “-rxbuffercnt” parsing for emIIRemote
- #5995 - Add support for ENIs without Config:ProcessImage element
- #5999 - Fix configured PDO to SyncManager assignment
- #6009 - Add support for ENIs without FMMU init commands
- #6078 - Reject complete access read for non complete access objects
- #6090 - Add support for packet capture files generated by TwinCAT Promiscuous Mode

### Platform

- #6094 - Add version and port print to RasSrvStart()
- #6030 - Add support for cable redundancy to emIIRemote
- #6026 - Add support for Raspberry Pi 5 to emIIGEM
- #6004 - Add Signature and Size to EC\_T\_RAS\_CLIENT\_CONDESC
- #5965 - Update RtaccWin V1.0.9
- #5963 - Generate SHA for delivery packages
- #5931 - Add promiscuous mode setting to emIISockRaw (“-promiscuousmode”)
- #5819 - Remove bpf dependency from emIISockXdp

- #5762 - Add bNoPhyAccess parameter to emllFslFec
- #5753 - Add default values for EC\_T\_RAS\_CLIENT\_CONDESC::dwCycleTime, dwWDTOLimit for em-RasClntAddConnection()
- #5686 - Refactor EcRasClient.h, EcRasServer.h to EcMasterRasClient.h, EcMasterRasServer.h, EcMonitor-RasServer.h, EcSimulatorRasClient.h, EcSimulatorRasServer.h
- #5306 - Fix support for MacOS
- #4564 - Add instance identification by PCI location for emllNdis
- #5408 - Add support for WAGO PFC200 and CC100 with Ethernet Switch Chip
- #5427 - Add support for ET2000 to emllMultiplier
- #5470 - Reduce timeout waiting for link connected in emllICSS
- #5659 - Add support for second port to emllCPSWG on Linux (Ti AM64x)
- #5747 - Add RAW mode to emllEom
- #5751 - Fix emllGem bNoPhyAccess
- #5769 - Add support for Xenomai4 ARM 64Bit
- #5809 - Add EC\_OS\_NAMESPACE
- #5889 - Add support for Intel X700 adapter family to emllDpdk
- #5901 - Add parameters for communication thread of RAS Client
- #5948 - Add armv7-vfp-eabi to Linux ARM 32Bit
- #5964 - Add emllDpdk for Linux ARM 64Bit
- #5977 - Add support for RK3576 and RK3562 to emllDW3504
- #5993 - Add Wrapper DLLs to RAS for Windows
- #6048 - Add ZEROCOPY Driver mode to emllSockXdp
- #6077 - Add UDP Mailbox Gateway Server to EC-Wrapper
- #6036 - Add workaround for I210 Errata 25 (Slow System Clock) to emllIntelGbe on VxWorks7
- #5929 - Fix LinkIoctl parameter interpretation of EC\_LINKIOCTL\_INTERRUPTENABLE, EC\_LINKIOCTL\_PROMISCUOUSMODE, EC\_LINKIOCTL\_GETLINKMODE, EC\_LINKIOCTL\_FORCELINKMODE
- #5743 - Merge EcLinkIoctl() in emllXXX
- #5735 - Remove deprecated mutex configuration in EcDemoMain.cpp for Linux
- #5549 - Fix occasional 5ms freeze in emllTiEnetCpswg on FreeRTOS
- #5775 - Fix compiler error due to INVALID\_SOCKET defined in EcOsPlatform.h on Linux
- #5805 - Fix emGetCfgSlaveInfo() over RAS on PPC
- #5808 - Fix emllIntelGbe link reconnect
- #5823 - Add support for INtime Distributed RTOS
- #5852 - Fix resource leak from interrupt initialization on VxWorks
- #5854 - Fix CRC error handling of emllDW3504 for GMAC4.x, ...
- #5866 - Fix crash in OsDeleteThreadHandle() on Linux with musl libc
- #5871 - Fix performance measurement becoming corrupted after 32Bit wrap on TI-RTOS
- #5882 - Fix access violation during emllCCAT initialization with invalid parameters
- #5899 - Fix GEM\_CLK\_CTRL handling to emllGEM on Ultrascale

- #5944 - Fix max frame len for emllTap
- #5801 - Update atemsys V1.4.32
  - Add support for dsa driver with Device Tree (insmod atemsys bRegisterDtbNetDevice=1)
  - Fix Device Tree support for Kernel > 6.1.00
  - Add support for TI AM64 CPSWG Second Port
- #5967 - Fix crash in RAS Server receiving malformed data during connection establishment
- #5975 - Fix crash in LinkOsInterruptDisable on VxWorks70 64Bit
- #5982 - Fix emRasGetConnectionInfo() returning wrong SPOC Information
- #5992 - Fix LinkOsUnmapMemory() on SylixOS
- #6029 - Set bind flags to XDP\_COPY and remove unneeded structures in emllSockXdp

## 3.6 V3.2.2.03

### Enhancement

- #5716 - Add support for emllDpdk to EC-Wrapper
- #5672 - Increase pcap recorder default buffer size from 50 to 1000 frames and write interval from 1ms to 50ms
- #5643 - Replace OsDbgAssert() with assert() in xmlparse.cpp
- #5532 - Add cmake build files for Linux

### Fixes

- #5696 - Use data type identifier 0x000A (DEFTYPE\_ARRAY\_OF\_BYTE) for data type name “ARRAY [0..XXX] OF of USINT” (DEFTYPE\_ARRAY\_OF\_USINT not defined in ETG.1020)
- #5671 - Fix memory leak in pcap recorder re-usage
- #5649 - Fix crash in emonGetSlaveInfo() if auto increment address outside boundaries
- #5481 - Fix missing EcMbxGatewaySrv.h in packages

### Platform

- #5707 - Add ATEMRAS\_T\_SRVPARMS::dwMaxQueuedNotificationSize
- #5694 - Add emllIntelGbe for QNX71 ARM\_32Bit
- #5670 - Add support for EC\_NOTIFY\_SLAVE\_STATECHANGED, EC\_NOTIFY\_SLAVE\_ERROR\_STATUS\_INFO to RAS Client on PPC
- #5635 - Update RtaccWin V1.0.8
- #5166 - Reduce Socket timeout if IP address is not available
- #4942 - Add emllEom supporting EtherCAT Open Mode
- #4590 - Add support for Xenomai4
- #5633 - Update atemsys V1.4.31
  - Set license to “SPDX-License-Identifier: GPL-2.0+ WITH Linux-syscall-note”
- #5688 - Add protocol version negotiation to emllRemote
- #5693 - Add device IDs for I219LM and I219V
- #5754 - Replace OsPrintf() with EcLogMsg() in EcSocket
- #5744 - Fix handling of EC\_T\_LINK\_PARAMS\_DW3504::dwRxDmaDesCnt, dwTxDmaDesCnt in emllDW3504

- #5702 - Reduce large memory allocations in RAS Server
- #5588 - Fix EcLinkOpen() sporadically returning EC\_E\_TIMEOUT in emllBcmGenet

## 3.7 V3.2.2.02

### Enhancement

- #5610 - Add mailbox error type processing
- #4198 - Add support for SuperSetEni

### Fixes

- #5609 - Fix bus scan detection in packet capture processing
- #5603 - Fix missing string termination in GetCfgSlaveEoeInfo(), GetSlaveProp() and CoeReadObjectDictionary() if string length equals buffer size
- #5582 - Support ENI with missing DataLength field of cyclic command

### Platform

- #5622 - Add EC-Master shared library for QNX
- #5577 - Add EC\_LINKIOCTL\_GET\_PCI\_INFO to emllIntelGbe for Windows and Linux
- #5562 - Add support for Semidrive D9 to emllDW3504
- #5548 - Add support for emllDW3504 on Intel Tiger-Lake
- #5639 - Fix CPU affinity for up to 64 cores
- #5626 - Fix link open failed in emllCCAT for some Beckhoff CX
- #5612 - Add RtaccDevice\_DmaFree() to Windows LinkOsFreeDmaBuffer()
- #5597 - Fix ecatGetSrcMacAddress() returns wrong MAC address if link down for emllCmsisEth
- #5412 - Update atemsys V1.4.30
  - Fix for Kernel > 6.4.00
  - Fix for systems without 32-bit DMA

## 3.8 V3.2.2.01

### Enhancement

- #5539 - Add EC\_IOCTL\_MONITOR\_SET\_COESDO\_CLEAR\_ON\_READ
- #5138 - Add “-readod ...”, “-readvars ...” to examples

### Fixes

- #5557 - Fix performance measurement: JOB\_Total was sometimes bigger than Task Duration (JOB\_Total + App)
- #5544 - Consider frame index in frame direction detection
- #5533 - Fix memory corruption if ENI file contains more than 64 cyclic frames
- #5522 - Fix unexpected MSU WKC state errors
- #5521 - Fix crash in emonBacktracePacketCapture if job task paused
- #5519 - Fix packet capture processing for frames bigger than 1536 bytes
- #5512 - Fix crash while monitoring fragmented CoE SDO info transfer

**Platform**

- #5543 - Add support for EC\_NOTIFY\_MBSLAVE\_COE\_SDO\_ABORT, EC\_NOTIFY\_SLAVE\_INITCMD\_RESPONSE\_ERROR, EC\_NOTIFY\_MBSLAVE\_INITCMD\_TIMEOUT, EC\_NOTIFY\_MASTER\_INITCMD\_RESPONSE\_ERROR to RAS on PPC
- #5515 - Add support for PENTIUM4llvm\_SMP on VxWorks70
- #5514 - Add support for EC\_NOTIFY\_SB\_MISMATCH, EC\_NOTIFY\_HC\_TOPOCHGDONE, EC\_NOTIFY\_FRAME\_RESPONSE\_ERROR, EC\_NOTIFY\_SLAVE\_PRESENCE, EC\_NOTIFY\_SLAVES\_PRESENCE to RAS Client on PPC
- #5498 - Add support for STM32H743 on uC3
- #5494 - Move AtXmlParser.cpp and .h to SourcesCommon
- #4072 - Add emllSockXdp (Linux AF\_XDP sockets)
- #5555 - Add missing notifications to marshalNotify() switch case that may cause an assertion failure
- #5552 - Fix crash in EC-Wrapper .NET with multiple RAS connections after first connection closed
- #5526 - Fix emllNdis interrupt mode (broken since V3.2.1.05)
- #5482 - Fix RAS Client performance issue
- #5467 - Fix occasional crash in emllCPSWG on Jacinto and AM654x

## 3.9 V3.2.1.05

**Enhancement**

- #5511 - Add support for EC\_T\_UINT64 (“0x%016lX”) to EcSprintf()
- #5504 - Add EC-Monitor for Linux ARM 64Bit

**Fixes**

- #5471 - Fix invalid read in emConfigureNetwork() in case of missing InitCmd comments
- #5391 - Fix notification handlers not called after first client deregistered
- #4925 - Replace assert() with OsDbgAssert() in xmlparse.cpp

**Platform**

- #5442 - Add support for Ti AM243x to emllTiEnetIcssg on FreeRTOS
- #5402 - Add QNX8 support
- #5368 - Update atemsys V1.4.29
  - Add support for TI AM64 CPSWG
  - Fix PCI dma\_coherent bit handling for Kernel between 4.15.0 and 5.4.0
- #5365 - Add PCI device IDs for Intel DWMAC 43a2 and 43ac
- #5364 - Add emllDW3504 for VxWorks x86
- #5355 - Add support for emllBcmNetXtreme to EC-Wrapper
- #5267 - Add support for RISC-V on Microchip Polar Fire
- #5266 - Add emllDpdk for Linux x86 64Bit
- #5265 - Add emllVlan
- #5236 - Replace EcatDrv with RtaccDevice
- #5208 - Add emllCPSWG on TI AM64x and TI AM62x

- #4983 - Add support to set frequency using OsMeasCalibrate() multiple times on Linux
- #4202 - Fix PHY initialization for 8168H/8111H in emllRTL8169
- #5347 - Enable bus master and memory space in PCI command register on QNX
- #5406 - Change name of TI Jacinto 7 from “TI J721E” (eCPSWG\_J721E) to “TI TDA4x (Jacinto 7)” (eCP-SWG\_TDA4X) in emllCPSWG
- #5445 - Add EC\_T\_LINK\_PARAMS\_DW3504::bNoPhyAccess for emllDW3504
- #5452 - Fix MAC Protected License Check in emllBcmGenet
- #5440 - Fix emllIntelGbe returns EC\_E\_NOMEMORY if cable redundancy and bResetOnDisconnect is used
- #5405 - Fix start with link disconnected for emllBcmNetXtreme
- #5404 - Fix LinkOsAllocDmaBuffer() fails on RtaccWin due to wrong RtaccWin InstanceID in case of multiple RtaccWin devices
- #5400 - Disable OsDbgAssert(...) in EcMonitor.dll on Windows
- #5359 - Fix undefined symbol LinkOsGetPciInfo in emllBcmNetXtreme for Linux
- #5340 - Fix legacy parameters handling in emllIntelGbe
- #5319 - Fix missing PCI info for Real-time Ethernet Drivers on Windows
- #4899 - Add OsReleaseLinkLayerRegFunc to Linux
- #5258 - Fix PHY handling in case of link disconnected for emllCPSW, emllDW3504, emllFslFec, emllGEM, emllICSS, emllRTL8169

## 3.10 V3.2.1.04

### Enhancement

- #5303 - Update Expat V2.6.0

### Platform

- #5334 - Add EC\_T\_LINK\_PARAMS\_INTELGBE::bNoPhyCtrlOnConnect to emllIntelGbe
- #5293 - Fix emllIntelGbe PHY reset blocked handling for I225, I350
- #5116 - Add emllBPF for QNX7.1
- #4920 - Change Real-time Ethernet Driver package nomenclature from “EC-Master-...”, “EC-Simulator-...” to “EC-RtEth-...”
- #5326 - Add EC\_COMPAREBITS
- #5340 - Fix legacy parameters handling in emllIntelGbe
- #5315 - Fix RX stucks in emllI8254x in case of frames exceeding buffer size
- #5335 - Fix memory corruption in RAS Server in emNotifyApp if dwInBufSize exceeds LARGEST\_NOTIFICATION

## 3.11 V3.2.1.03

### Enhancement

- #5274 - Set calling convention at callback function types
- #5270 - Add support for SylixOS on ARM64
- #5094 - Add emonGetSlaveInpVarByObjectEx(), emonGetSlaveOutpVarByObjectEx()
- #4844 - Add support for Codesys EtherCAT Master
- #5189 - Improve hash table performance

### Fixes

- #5307 - Fix Kunbus TAP Curious support
- #5295 - Fix invalid read in EC\_COPYBITS at end of pbySrc
- #5177 - Fix missing update of MonitorOD after slave address change

### Platform

- #5238 - Add support for emGetSlaveInpVarByObjectEx() and emGetSlaveOutVarByObjectEx() to RAS
- #5225 - Add support for TI J721E to emllCPSWG
- #5195 - Add emRasSrvSetLogParms()
- #5070 - Add emllTap
- #4964 - Add support for TI CPSWG AM6x and Jacinto 7 (j784s4) based on Enet LLD on FreeRTOS (emll-TiEnetCpswg)
- #4927 - Add support for AMD Xilinx Vitis on FreeRTOS
- #4846 - Add support for TI AM65x to emllCPSWG on Linux
- #5176 - Add EC\_LINKIOCTL\_SET\_MSECCOUNTERPTR to emllGEM
- #5183 - Add emllDW3504 for Xenomai3 ARM\_64Bit
- #5193 - Add support for EC\_NOTIFY\_CLIENTREGISTRATION\_DROPPED, EC\_NOTIFY\_CYCCMD\_WKC\_ERROR, EC\_NOTIFY\*\_INITCMD\_WKC\_ERROR, EC\_NOTIFY\_COE\_MBXSND\_WKC\_ERROR, EC\_NOTIFY\_SLAVE\_NOT\_ADDRESSABLE, EC\_NOTIFY\*\_ALL\_DEVICES\_OPERATIONAL to RAS client on PPC
- #5199 - Add device IDs for I219LM and I219V
- #5242 - Add support for emUnregisterClient(), EC\_IOCTL\_UNREGISTERCLIENT to RAS Client on PPC
- #5252 - Update atemsys V1.4.28
  - Fix PCIe compatibility for atemsys < V1.3.5
  - Fix support for Kernel > 6.05.00
  - Fix ATEMSYS\_IOCTL\_CPSWG\_CMD Kernel version
  - Add support for Device Tree Ethernet driver to CPSWG
  - Fix support for arm/aarch64 Kernel >= 6.00.00
  - Fix of\_dma\_configure version
  - Add ATEMSYS\_IOCTL\_IOMEM\_CMD for Kernel mode access to protected registers
  - Add ATEMSYS\_IOCTL\_CPSWG\_CMD to configure K3\_UDMA\_CPSWG channels, flows and rings
- #5256 - Add emllRemote for Linux, Windows
- #5314 - Fix OsWaitForEvent(..., dwTimeout) on RTOS-32

- #5259 - Fix missing DLLs in EC-STA packages
- #5239 - Fix dependency of compiled OsLayer to Sources/OsLayer on Windows
- #5223 - Deactivate Filters in the NDIS driver
- #5108 - Fix emCoeGetODList(), emCoeGetObjectDesc(), emCoeGetEntryDesc() for RAS Client on PPC
- #5181 - Remove duplicate warning of missing PREEMPT RT patch on Linux
- #5200 - Fix long timeout at RAS Client disconnection after socket shutdown
- #5201 - Fix emNotifyApp() over RAS without emRegisterClient() at RAS Client
- #5229 - Fix EcMbxGatewayClnt uploads not existing object for internal config slave cache
- #5230 - Fix EcMbxGatewayClnt logging (EC\_T\_MBX\_GATEWAY\_CLNT\_CONDESC::LogParms)
- #5240 - Fix erroneously deregister client in RAS Server for previously dropped client
- #5243 - Fix RAS Client EC\_LOG\_LEVEL\_INFO\_API logging

## 3.12 V3.2.1.02

### Enhancement

- #5133 - Add eEthTap\_PortMirror
- #5064 - Add emonTferSingleRawCmd to support register read via RAS
- #4146 - Add swap data support
- #5088 - Add application performance measurements to CSV output

### Fixes

- #5136 - Fix emonGetSlaveFixedAddr() for MASTER\_SLAVE\_ID
- #5120 - Fix timing task CPU affinity
- #5099 - Fix potential naming conflict of Expat library
- #5077 - Fix crash if ENI contains no logical commands
- #5066 - Fix missing refresh of EC\_T\_SLVSTATISTICS\_DESC::wAIStatusCode
- #5006 - Fix erroneous EC\_NOTIFY\_FRAME\_RESPONSE\_ERROR in case of mailbox repeating
- #5059 - Fix emonBacktracePacketCapture in case of packet capture processing and job task paused
- #5076 - Fix console logging freeze on RTOS-32 (regression since V3.1.4.05)
- #5093 - Fix cycle time performance measurement is implemented in eUsrJob\_SendAllCycFrames instead of eUsrJob\_StartTask (regression since V3.1.2.03)
- #5125 - Fix registered client lookup on notification
- #5127 - Fix missing string termination in SDO value log message of DEFTYPE\_VISIBLESTRING in CoeReadObjectDictionary() in examples
- #5128 - Fix Master OD reading canceled at RX PDO mapping and TX PDO mapping in CoeReadObjectDictionary() in examples

### Platform

- #5051 - Remove support for T-Kernel and eT-Kernel
- #4985 - Add FP Real-time Accelerator for Windows
- #4641 - Add support for Broadcom BCM5719 (emllBcmNetXtreme)

- #4245 - Remove obsolete EC\_LINKIOCTL\_REGISTER\_FRAME\_CLBK, EC\_LINKIOCTL\_UNREGISTER\_FRAME\_CLBK
- #4909 - Add MAC Protection for Rockchip RK3588 and RK3568
- #4937 - Use poll() or epoll() instead of select() for sockets
- #4943 - Add support for i.MX93 to emllFslFec
- #4965 - Fix support for KSZ9131 (disable EEE in Phylib)
- #5042 - Add EC\_T\_LINK\_PARAMS\_GEM::bNotUseCacheSync to fix performance issue with emllGEM e.g. on older systems by disabling internal LinkOsCacheDataSync() (default: enabled)
- #5053 - Add support for MAC protection to emllDW3504 on Rockchip RK3399
- #5097 - Fix crash in rt\_task\_inquire due to bug in Xenomai3 API
- #4972 - Fix emllIntelGbe EcLinkGetSpeed()
- #4872 - Fix DW3504 Altera Cyclone Performance issue by turn off cache sync
- #4967 - Fix memory leak in emllAlteraTSE
- #4984 - Fix emRasSrvStop hangs on EC-Win(RTOS-32)
- #4995 - Configure TTS interrupt only if EC\_T\_LINK\_PARAMS\_ICSS::TtsParams::pfnStartCycle set
- #5001 - Fix emllRZT1 MAC address reset
- #5014 - Fix RAS server on RTX64 (broken since V3.1.4.01)
- #5065 - Fix threading on TI-RTOS AM65x (e.g. RAS server starved)

### 3.13 V3.2.1.01

#### Enhancement

- #4894 - Add CopyInfo to EC\_T\_PROCESS\_VAR\_INFO
- #4805 - Change IPv4 parameter variables type from EC\_T\_DWORD to EC\_T\_IPADDR
- #4612 - Remove legacy performance measurement APIs
- #4946 - Add pdwVersionType parameter to emonGetVersion()
- #4891 - Add EC\_T\_MONITOR\_STATUS::eEthTapType
- #4525 - Rename RAS client and server to EcMonitorRasClient and EcMonitorRasServer
- #4017 - Rename emPerfMeasInternalXxx to emPerfMeasXxx

#### Fixes

- #4881 - Fix erroneous detection of RX frames as TX for Wireshark traces containing only RX frames.
- #4987 - Fix crash in emonCoeSdoUpload if CoE storage and notification disabled
- #4919 - Fix reentrancy of emInitMonitor() after emInitMonitor() was called with bad parameters
- #4913 - Fix crash in EcLinkFreeRecvFrame for some Real-time Ethernet Drivers

#### Platform

- #4972 - Fix emllIntelGbe EcLinkGetSpeed()
- #4971 - Add pdwSpeed parameter to EcLinkGetSpeed
- #4950 - Add support for 64Bit DMA physical address on INtime6
- #4855 - Add szLoadPath to EC\_T\_LINK\_PARAMS
- #4837 - Add QNX SMMUMAN support

- #4726 - Add support for Rockchip DW3504
- #4718 - Add support for IRQ CPU affinity on Linux
- #4626 - Add device IDs for Intel Pro/1000 (i8254x) I226
- #4611 - Add support for Xilinx KR260 SGMII Port
- #4956 - Fix INVALID\_STATE in CEcWrapperDotNet::DeinitInstance() if started with MbxGatewaySrv
- #4882 - Add support for SGMII on Marvell 88E1510 for Intel DW3504
- #4859 - Fix DW3504 Rockchip Clocks and second Instance
- #4784 - Fix EcatDrv to support KeTimer period < 16ms

## 3.14 V3.2.0.03

### Enhancement

- #4848 - Use default TaskId 0 if eUsrJob\_StartTask called with EC\_NULL
- #4833 - EC\_COPYBITS\_INLINE declare EC\_T\_BYTE\* pbySrc as const
- #4879 - Add EC-Monitor QNX71 support
- #4188 - Add emonReadSlaveRegister

### Fixes

- #4877 - Fix IntelGbe EclinkOpen() faulty log messages
- #1899 - Fix RAS protocol corruption in case of concurrent send requests at server
- #4810 - Fix crash in EC-Wrapper .NET if variable size exceeds 512 bytes
- #4875 - Fix text translation crash in EC-Wrapper
- #4774 - Fix bit offset of process variables Inputs.DevicesState and Inputs.BusTime
- #4810 - Fix crash in EC-Wrapper .NET if variable size exceeds 512 bytes
- #4875 - Fix text translation crash in EC-Wrapper EtherCAT Network Monitoring

### Platform

- #4804 - Add Device ID for Intel Pro/1000 I82545EM Copper
- #4820 - Update atemsys V1.4.25
  - Add IOCTL\_INT\_CPU\_AFFINITY
  - Add Device Tree Ethernet driver support for RockChip

## 3.15 V3.2.0.02

### Enhancement

- #4605 - Add “-maxbusslaves” parameter to examples
- #4724 - Prolong Eval time limit from 10 to 30 minutes
- #4703 - Enhance frame direction detection
- #4685 - Add pcap file name support to EcMonitorDemo

### Fixes

- #4737 - Fix value distribution for min and max bin in performance measurement histogram

- #4708 - Remove systematic delay of 250ms within emConfigLoad(), emConfigureMaster(), emConfigExtend(), emDeinitMaster(), emRescueScan(), emSelfTestScan()
- #4768 - Fix frame processing in case of all RX frames missing
- #4754 - Fix incomplete wireshark trace recordings
- #4702 - Fix crash in case of multiple cyclic entry ENI

#### Platform

- Microsoft® Windows® Visual Studio® project files updated to VS2015
- #4704 - Add EC\_T\_LINK\_PARAMS::dwLinkSpeed
- #4709 - Add support for STM32MP135 to DW3504
- #4691 - Add support for ecatNotifyApp() from RAS Server application to RAS Client application
- #4690 - Change connection type from UDP to TCP for emllProxy
- #4764 - Fix memory leak in RAS Client if connection lost while EoE-Endpoint active
- #4755 - Fix EC\_COPYBITS out-of-bounds read from pbySrc
- #4731 - Update atemsys V1.4.24
  - Fix PCI bars
  - Add Device Tree Ethernet driver support for STM32mp135

## 3.16 V3.2.0.01

#### Enhancement

- #4434 - Change EC-Monitor API Prefix from “em” to “emon”

#### Platform

- #4338 - Add IstStackSize to all Linklayers parameters
- #4331 - Change Mutex default setting for Linux
- #4665 - Update atemsys V1.4.22
  - Fix Build Warnings
  - Fix kernel config depending irq structures
  - Fix kernel version 4.12 to 4.15 for handle of dma\_coherent bit
  - Add IOMMU support, new mapping to userspace active and tested for kernel > 5.4, use old mapping with ATEMSYS\_LEGACY\_DMA=1 define or activate new mapping with ATEMSYS\_LEGACY\_DMA=0 define for older kernel

## 3.17 V3.1.4.06

- Add emStartLivePacketCapture to EcMonitorDemo
- Add support for fragmented CoE SDO Info mailbox transfers
- Fix read multiple \*.pcap files
- Fix frame type (cyclic/acyclic) detection if cyclic frame contains NOP commands
- Fix rebuild topology from bus scan failed in packet capture processing mode
- Add emNotify - eMbxTferType\_COE\_GETODLIST

- Add slave station address to EC\_T\_COE\_ENTRYDESC, EC\_T\_COE\_OBDESC and EC\_T\_COE\_ODLIST
- Add frame response error type eRspErr\_CRC
- Remove BlockNode handling from CEmNotification
- Fix slave information prints contain “ERROR: Not found” in examples
- Fix crash in case of invalid ENI containing a hot connect group head slave with physical address equal to zero
- Increase log buffer in examples

#### Platform

- Force disconnection using PHY loopback for emllI8254x if ResetOnDisconnect not set
- Add support for emllTiEnetIcsg on AM64xEVM with FreeRTOS
- Add emllDW3504 for Xenomai
- Select ‘ECAT Protocol Driver’ installation on Windows by default if not currently installed
- Fix PCI link layer support for QNX ARM 32 Bit
- Add DCM MasterShift for QNX
- Add support for emllGEM on Xilinx Kria KR260
- Fix missing ATEMRAS\_NOTIFY\_CONNECTION EMRAS\_EVT\_SERVERSTOPPED on connection termination by server
- Fix TX hang in emllI8254x for I219 after uncontrolled termination
- Fix lock-up in EC-Wrapper RAS connection on termination by server
- Set default stack size to 0x8000 for 64 Bit architectures

### 3.18 V3.1.4.05

- Add histogram export to examples
- Fix no messages in error log if NOPRINTF defined

#### Platform

- Add emllBcmGenet for Raspberry PI 4 (BCM2711)
- Fix reset MAC address at DW3504
- Fix memory leak in OsCreateEvent() on Linux, Xenomai, RTEMS and SylixOs in case of semaphore initialization error

### 3.19 V3.1.4.04

- Add Hilscher netANALYZER Ethernet TAP support
- Enhance Live Packet Capture
- Add emNotify - eMbxTferType\_COE\_GETENTRYDESC

#### Platform

- Add support for VxWorks70

### 3.20 V3.1.4.03

- Add packet capture processing command line option “-play”
- Add “-oem” command line parameter to examples
- Fix FoE monitoring in Bootstrap
- Extend pcap file format support (nanosecond pcap)
- Add FoE monitoring support
- Add interrupt support

#### Platform

- Increase resolution for OsSystemTimeGet() on Windows
- Add bDisablePromiscuousMode and bDisableForceBroadcast parameters to emllNdis
- Add absolute path support alternative to OsGetLinkLayerRegFunc for VxWork70
- Fix counter overrun in OsQueryMsecCount on VxWorks69 PENTIUM4
- Fix RTOS-32 is not supporting cycle times below 1000us (broken since V3.1.1.06)
- Fix occasional crash in RAS Server on EC\_IOCTL\_UNREGISTERCLIENT
- Fix occasional crash on emRasClntRemoveConnection after emRasSrvStop
- Fix Interrupt Mode support for emllProxy
- Fix Multi Tasks Configuration doesn't work with emllNdis Linklayer
- Fix memory leak on RAS socket disconnect while API call pending
- Fix to block emRasClntRemoveConnection, emRasSrvStop until all worker threads terminated

### 3.21 V3.1.4.02

- Add emGetSlaveInfo
- Add performance measurement level to -perf command line parameter
- Add emGetMemoryUsage over RAS
- Fix topology after reconnect/restart/communication timeout
- Fix EC\_NOTIFY\_TAP\_LINK\_STATUS in interrupt mode
- Fix CoE response and abort handling
- Fix blocking API handling over RAS

#### Platform

- Add MAC protection to emllFslFec for i.MX8 and i.MX8m
- Fix CPSW transmit channels to work with acontis CPSW Linux driver patch
- Fix command line contains unexpected application name in RTOS-32 config files

## 3.22 V3.1.4.01

- Add notifications:
  - EC\_NOTIFY\_PDIWATCHDOG
  - EC\_NOTIFY\_STATUS\_SLAVE\_ERROR
  - EC\_NOTIFY\_SLAVE\_ERROR\_STATUS\_INFO
  - EC\_NOTIFY\_SLAVE\_STATECHANGED
  - EC\_NOTIFY\_CYCCMD\_WKC\_ERROR
- Fix bus load average 0 in case of Monitor and Master run with different cycle times
- Fix unfilled MbxData after emCoeGetODList
- Don't call OsMeasCalibrate() if performance measurement is disabled
- Rename PerfMeas distances to offsets

### Platform

- Fix i8254x interrupt mode on ARM/AARCH64
- Updated to ECAT NDIS Protocol Driver Setup V3.1.3.4. Hide command window during driver installation
- Updated to atemsys V1.4.20
  - Fix support for CMA (Contiguous Memory Allocator) for kernel > 4.9.00

## 3.23 V3.1.3.03

- Add EC\_T\_MASTER\_INFO::dwMasterStateSummary
- EC\_T\_MASTER\_INFO::BusDiagnosisInfo data available even if compiled with EXCLUDE\_MASTER\_OBD
- Add EC\_IOCTL\_SET\_NOTIFICATION\_ENABLED and EC\_IOCTL\_GET\_NOTIFICATION\_ENABLED
- Add MasterSyncUnit support
- Fix interrupt mode support
- Add EC\_T\_PACKETCAPTURE\_PARAMS::bReadMultipleFiles for emOpenPacketCapture()
- Cycle time and JOB\_Total timer missing in EcSimulator since V3.1.2.10

### Platform

- Updated to atemsys V1.4.18
  - Remove obsolete ARM cycle count register(CCNT)
  - Fix PCI driver do registration for all Ethernet network adapters
  - Add modul parameter AllowedPciDevices to adjust PCI driver
- Add CPU affinity support to Link Layers supporting interrupt mode

### 3.24 V3.1.3.02

- Support ENI file with CU2508 only
- Add support for emCoeGetODList
- Add EC\_T\_MONITOR\_STATUS::bNextCyclicEntryReceived, rename EC\_T\_MONITOR\_STATUS::bFramesInLinkLayerPen to bNextFramesReceived
- Add EC\_NOTIFY\_SB\_STATUS, EC\_NOTIFY\_SB\_MISMATCH
- Fix build topology immediately in packet capture processing mode
- Add process data input mapping for Inputs.BusTime and Inputs.DevicesState

#### Platform

- Add RTL8168H support to emllRTL8169
- Fix DMA buffer alignment in emllRTL8169 (regression since V3.1.3.01)
- Fix DMA allocation, requesting memory below 4GB for AARCH64/ARM64 on QNX
- Updated to ECAT NDIS Protocol Driver V3.1.3.2  
Move promiscuous mode setting from NDIS Link-Layer to NDIS protocol driver  
Add an entry “DontSetPromiscuousMode” in the Windows registry to avoid setting promiscuous mode in ECAT NDIS Protocol Driver  
Rename Setup to “ECAT NDIS Protocol Driver”
- Fix EcatDrvGetDrvVersion on Windows (regression since V3.1.3.01)
- Add RTL8125 support to emllRTL8169
- Updated to atemsys V1.4.17.  
Fix atemsys dma\_set\_mask\_and\_coherent() missing in kernels under 3.12.55
- NDIS fix start-up with link disconnected

### 3.25 V3.1.3.01

- Add the InitMonitor parameter dwMbxRecordBufferSize to specify a buffer size for Mailbox recordings
- Fix crash on Xenomai when recording a Coe Object dictionary

### 3.26 V3.1.2.11

- Fix unset eMbxTferType in COE SDO upload notification when using emCoeSdoUploadReq
- Add EC\_NOTIFY\_COMMUNICATION\_TIMEOUT and EC\_NOTIFY\_TAP\_LINK\_STATUS
- Add EC\_T\_MONITOR\_INIT\_PARMS::bApiLockByApp
- Add WKC State Support

### 3.27 V3.1.2.10

- Extend EC\_T\_FRAME\_RSPERR\_DESC with wCycFrameNum and dwTaskId
- Fix emGetBusSlaveInfo returns EC\_E\_NOTFOUND if called with autoinc addressing for some hot-connect configurations

### 3.28 V3.1.2.09

- Fix CoE Emergency notification
- Fix high CPU load in eUsrJob\_MasterTimer
- Fix emGetSlaveState in case of slave is not present

### 3.29 V3.1.2.08

- Enhance Hot-Connect support to detect groups on master start-up
- Add EC\_NOTIFY\_MBOXRCV notification for emCoeSdoUploadReq
- Add API emHCGetSlaveIdsOfGroup and emHCGetNumGroupMembers
- Store eMbxTferType\_COE\_SDO\_DOWNLOAD and eMbxTferType\_COE\_SDO\_UPLOAD in object dictionary accessible through emCoeSdoUpload

### 3.30 V3.1.2.07

- Add EC\_NOTIFY\_MBOXRCV for eMbxTferType\_COE\_SDO\_DOWNLOAD and eMbxTferType\_COE\_SDO\_UPLOAD
- Enable jumbo frame support for i8254x by default
- Enhance Hot-Connect support to detect connection and disconnection of Hot-Connect groups
- Enhance cycle/frame loss detection in states INIT, PREOP and during transitions

### 3.31 V3.1.2.06

- Fix cycle/frame loss detection for cyclic tasks with more than one frame
- emGetSlaveState returns the current and requested state accordingly to AL-Control, AL-Status respectively

### 3.32 V3.1.2.05

- Add PCAP file format support for “Nokia tcpdump” and “Modified tcpdump”
- Fix Object 0x2001 “Master State Summary”, Bit 10: Bus Scan Match and Bit 16: Link Up
- Add PCAPNG file format support
- Add position independent ethernet tap support
- Fix link status after emInitMonitor

### 3.33 V3.1.2.04

- Fix emGetMonitorParms

### 3.34 V3.1.2.03

- Add EC\_IOCTL\_GET\_CYCLIC\_CONFIG\_INFO, EC\_IOCTL\_IS\_SLAVETOSLAVE\_COMM\_CONFIGURED, EC\_IOCTL\_CLR\_SLVSTATISTICS
- Fix emGetSlaveInpVarInfoEx, emGetSlaveOutpVarInfoEx
- Add QNX7 support
- Add basic hot connect topologies support

### 3.35 V3.1.2.02

- Add emIsSlavePresent, EC\_IOCTL\_ISLINK\_CONNECTED, EC\_IOCTL\_GET\_LINKLAYER\_MODE
- Fix performance measurement in EcMonitorDemo
- Fix invisible slave handling
- Add Xenomai3 support
- Add emGetMonitorStatus
- Add emBacktracePacketCapture

### 3.36 V3.1.2.01

- Change emOpenPacketCapture parameter set
- Add emStartLivePacketCapture, emStopLivePacketCapture
- EcMonitorDemo exclude EcDaq dependency
- Add Object 0x2200 “Bus Load” support
- Fix Object 0x2002:03 “Bus Diagnosis”

### 3.37 V3.1.1.07

- Add Object 0x2001 “Master State Summary”, Bit 8: Slaves in requested State

### **3.38 V3.1.1.06**

- Initial release of EC-Monitor